Reported	Calculated	Formula for le	alculated	
rayor car		Copper.		
	899 or-01		8983 = -014	
9904	0014	90+10+	9912 \$ -	ivapio
	11.	· +/1.5 x x x 5	19 3	
3/4	2	1.54.25	992, 3	
991	992 (100=	8.) 90+1.+1.	2 + 20°	00000
4	4 1 2	100 - 7=	1 2 2 2 E	2,600
990-234	991 4 12 24 100= 4 12 24 100= 4	90+1.5+1.25	30x 60/100 20 20 20 20 20 20 20 20 20 20 20 20 2	6 . 6 . 6 . 6 . 6 . 6 . 6 . 6 . 6 . 6 .
992	993 4 2 24 4 2 24	100-7	3,00	3
4	11 4	90+3+4	6	6
2	. 1	90+3+2	- 2 41	i i
992	9944	100-6	ररं०६	12 med
	1174	90+24+1+1	to a l	
1/2	支	90 +42	3	
2 4	3 4	90+24+(2.4)	i en	= Ke
994	995	100-5	3	
1	995	90+4.5+.75	3 = 5	H
994	2	90+45+10+25	74-14-14	.0004 in furnell
105	996 4		2000	13
995 4	11 +	90+3+3+25		4000
+ 2	3	90+1.5+5	3	0.
24	905	100-3	4	3
996	997 4	90+45+2.25+.50	lavee	lowe
2004	1 2	100-2½ or 90+7:5	73	to be lower te
	0,00	40+7.5+.25 0100-24	\$ 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	
997	998 \$	90+7:5+75		35 5
1	2	100-15 - 90 +75+1.	1500	70000
* 12 3 4	3 4	90 +75+ 1.25 0 100-14	5 \$ 5	3000000
998 4	999	90,49 00 190-1	2	
Control of the Contro		1'0075	3,	
1 2 3 4	2 3	100-50 0090+4.5+5.	m m	
	1000 4	100-25 90+75+2125	For a mel	000.
999 ;	4	100+ 025	£ 3°	1440
1 2 3	<b></b>	100+.5	4	-
34	3 4	100.+.75		